

Right to Know **ealth** Hazardous Substance Fact Sheet

SODIUM BROMATE Common Name:

Synonyms: None

Chemical Name: Bromic Acid, Sodium Salt

Date: August 1999 Revision: March 2009

Description and Use

Sodium Bromate is a colorless to white, crystalline (sand-like) or granular, odorless powder. It is used in gold ore precessing, as an analytical reagent and boiler cleaner, and in hair preparations.

Reasons for Citation

▶ Sodium Bromate is on the Right to Know Hazardous Substance List because it is cited by DOT.

SEE GLOSSARY ON PAGE 5.

FIRST AID

Eye Contact

▶ Immediately flush with large amounts of water for at least 15 minutes, lifting upper and lower lids. Remove contact lenses, if worn, while rinsing.

Skin Contact

▶ Quickly remove contaminated clothing. Immediately wash contaminated skin with large amounts of water.

Inhalation

- ▶ Remove the person from exposure.
- ▶ Begin rescue breathing (using universal precautions) if breathing has stopped and CPR if heart action has stopped.
- ▶ Transfer promptly to a medical facility.
- ▶ Medical observation is recommended for 24 to 48 hours after overexposure, as pulmonary edema may be delayed.

EMERGENCY NUMBERS

Poison Control: 1-800-222-1222 CHEMTREC: 1-800-424-9300 NJDEP Hotline: 1-877-927-6337

National Response Center: 1-800-424-8802

CAS Number: 7789-38-0

RTK Substance Number: 1686 DOT Number: UN 1494

EMERGENCY RESPONDERS >>>> SEE LAST PAGE

Hazard Summary **NJDOH NFPA** 2

Hazard Rating **HEALTH FLAMMABILITY** 0 **REACTIVITY** 0

STRONG OXIDIZER POISONOUS GASES ARE PRODUCED IN FIRE CONTAINERS MAY EXPLODE IN FIRE

Hazard Rating Key: 0=minimal; 1=slight; 2=moderate; 3=serious;

- ▶ Sodium Bromate can affect you when inhaled.
- ▶ Contact can irritate the skin and eyes.
- ▶ Sodium Bromate can irritate the nose and throat.
- ▶ Inhaling **Sodium Bromate** can irritate the lungs. Higher exposures may cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency.
- ▶ Exposure to **Sodium Bromate** can cause vomiting, diarrhea, stomach pain, and restlessness.
- ▶ High levels of this substance can reduce the blood's ability to transport Oxygen, causing headache, fatigue, dizziness, and a blue color to the skin and lips (methemoglobinemia).
- ▶ Repeated exposure to high levels may affect the inner ear leading to ringing in the ears and hearing loss.
- ▶ Sodium Bromate may damage the kidneys.
- ▶ Sodium Bromate is not combustible, but it is a STRONG OXIDIZER that enhances the combustion of other substances.

Workplace Exposure Limits

No occupational exposure limits have been established for Sodium Bromate. However, it may pose a health risk. Always follow safe work practices.

SODIUM BROMATE Page 2 of 6

Determining Your Exposure

- ▶ Read the product manufacturer's Material Safety Data Sheet (MSDS) and the label to determine product ingredients and important safety and health information about the product mixture.
- ► For each individual hazardous ingredient, read the New Jersey Department of Health Hazardous Substance Fact Sheet, available on the RTK website (www.nj.gov/health/eoh/rtkweb) or in your facility's RTK Central File or Hazard Communication Standard file.
- ➤ You have a right to this information under the New Jersey Worker and Community Right to Know Act, the Public Employees Occupational Safety and Health (PEOSH) Act if you are a public worker in New Jersey, and under the federal Occupational Safety and Health Act (OSHA) if you are a private worker.
- ▶ The New Jersey Right to Know Act requires most employers to label chemicals in the workplace and requires public employers to provide their employees with information concerning chemical hazards and controls. The federal OSHA Hazard Communication Standard (29 CFR 1910.1200) and the PEOSH Hazard Communication Standard (N.J.A.C. 12:100-7) require employers to provide similar information and training to their employees.

This Fact Sheet is a summary of available information regarding the health hazards that may result from exposure. Duration of exposure, concentration of the substance and other factors will affect your susceptibility to any of the potential effects described below.

Health Hazard Information

Acute Health Effects

The following acute (short-term) health effects may occur immediately or shortly after exposure to **Sodium Bromate**:

- ► Contact can irritate the skin and eyes.
- Sodium Bromate can irritate the nose and throat causing coughing and wheezing.
- ▶ Inhaling Sodium Bromate can irritate the lungs causing coughing and/or shortness of breath. Higher exposures may cause a build-up of fluid in the lungs (pulmonary edema), a medical emergency, with severe shortness of breath.
- ► Exposure to **Sodium Bromate** can cause vomiting, diarrhea, stomach pain, and restlessness.
- ► High levels of this substance can reduce the blood's ability to transport Oxygen, causing headache, fatigue, dizziness, and a blue color to the skin and lips (methemoglobinemia). Exposure to very high levels can cause trouble breathing, collapse and even death.

Chronic Health Effects

The following chronic (long-term) health effects can occur at some time after exposure to **Sodium Bromate** and can last for months or years:

Cancer Hazard

According to the information presently available to the New Jersey Department of Health, Sodium Bromate has not been tested for its ability to cause cancer in animals.

Reproductive Hazard

▶ While **Sodium Bromate** has been tested, further testing is required to assess its potential to cause reproductive harm.

Other Effects

- ▶ Repeated exposure to high levels may affect the inner ear leading to ringing in the ears and hearing loss.
- Sodium Bromate can irritate the lungs. Repeated exposure may cause bronchitis to develop with coughing, phlegm, and/or shortness of breath.
- ▶ Sodium Bromate may damage the kidneys.

Medical

Medical Testing

If symptoms develop or overexposure is suspected, the following are recommended:

- ► Consider chest x-ray after acute overexposure
- ▶ Blood methemoglobin level
- ► Kidney function tests
- ▶ Hearing test

Any evaluation should include a careful history of past and present symptoms with an exam. Medical tests that look for damage already done are <u>not</u> a substitute for controlling exposure.

Request copies of your medical testing. You have a legal right to this information under the OSHA Access to Employee Exposure and Medical Records Standard (29 CFR 1910.1020).

Mixed Exposures

► Smoking can cause heart disease, lung cancer, emphysema, and other respiratory problems. It may worsen respiratory conditions caused by chemical exposure. Even if you have smoked for a long time, stopping now will reduce your risk of developing health problems.

SODIUM BROMATE Page 3 of 6

Workplace Controls and Practices

Very toxic chemicals, or those that are reproductive hazards or sensitizers, require expert advice on control measures if a less toxic chemical cannot be substituted. Control measures include: (1) enclosing chemical processes for severely irritating and corrosive chemicals, (2) using local exhaust ventilation for chemicals that may be harmful with a single exposure, and (3) using general ventilation to control exposures to skin and eye irritants. For further information on workplace controls, consult the NIOSH document on Control Banding at www.cdc.gov/niosh/topics/ctrlbanding/.

The following work practices are also recommended:

- ▶ Label process containers.
- ▶ Provide employees with hazard information and training.
- ▶ Monitor airborne chemical concentrations.
- Use engineering controls if concentrations exceed recommended exposure levels.
- ▶ Provide eye wash fountains and emergency showers.
- Wash or shower if skin comes in contact with a hazardous material.
- ▶ Always wash at the end of the workshift.
- Change into clean clothing if clothing becomes contaminated.
- ▶ Do not take contaminated clothing home.
- ▶ Get special training to wash contaminated clothing.
- ▶ Do not eat, smoke, or drink in areas where chemicals are being handled, processed or stored.
- ► Wash hands carefully before eating, smoking, drinking, applying cosmetics or using the toilet.

In addition, the following may be useful or required:

Use a vacuum or a wet method to reduce dust during cleanup. DO NOT DRY SWEEP.

Personal Protective Equipment

The OSHA Personal Protective Equipment Standard (29 CFR 1910.132) requires employers to determine the appropriate personal protective equipment for each hazard and to train employees on how and when to use protective equipment.

The following recommendations are only guidelines and may not apply to every situation.

Gloves and Clothing

- ▶ Avoid skin contact with **Sodium Bromate**. Wear personal protective equipment made from material which can not be permeated or degraded by this substance. Safety equipment suppliers and manufacturers can provide recommendations on the most protective glove and clothing material for your operation.
- Safety equipment manufacturers recommend Nitrile and Natural Rubber for gloves, and Tyvek®, or the equivalent, as a protective material for clothing.
- ▶ All protective clothing (suits, gloves, footwear, headgear) should be clean, available each day, and put on before work.

Eye Protection

- ▶ Wear eye protection with side shields or goggles.
- ▶ If additional protection is needed for the entire face, use in combination with a face shield. A face shield should not be used without another type of eye protection.

Respiratory Protection

Improper use of respirators is dangerous. Respirators should only be used if the employer has implemented a written program that takes into account workplace conditions, requirements for worker training, respirator fit testing, and medical exams, as described in the OSHA Respiratory Protection Standard (29 CFR 1910.134).

- At any detectable concentration, use a NIOSH approved negative pressure, air-purifying, particulate filter respirator with an N, R or P95 filter. More protection is provided by a full facepiece respirator than by a half-mask respirator, and even greater protection is provided by a powered-air purifying respirator.
- ▶ Leave the area immediately if (1) while wearing a filter or cartridge respirator you can smell, taste, or otherwise detect **Sodium Bromate**, (2) while wearing particulate filters abnormal resistance to breathing is experienced, or (3) eye irritation occurs while wearing a full facepiece respirator. Check to make sure the respirator-to-face seal is still good. If it is, replace the filter or cartridge. If the seal is no longer good, you may need a new respirator.
- ► Consider all potential sources of exposure in your workplace. You may need a combination of filters, prefilters or cartridges to protect against different forms of a chemical (such as vapor and mist) or against a mixture of chemicals.
- ▶ Where the potential for high exposure exists, use a NIOSH approved supplied-air respirator with a full facepiece operated in a pressure-demand or other positive-pressure mode. For increased protection use in combination with an auxiliary self-contained breathing apparatus operated in a pressure-demand or other positive-pressure mode.

Fire Hazards

If employees are expected to fight fires, they must be trained and equipped as stated in the OSHA Fire Brigades Standard (29 CFR 1910.156).

- Sodium Bromate is not combustible, but it is a STRONG OXIDIZER that enhances the combustion of other substances.
- ► Use water only. DO NOT USE DRY CHEMICAL or CO₂ extinguishing agents.
- ► POISONOUS GASES ARE PRODUCED IN FIRE, including Hydrogen Bromide.
- ► CONTAINERS MAY EXPLODE IN FIRE.
- ▶ Use water spray to keep fire-exposed containers cool.
- ► Sodium Bromate may ignite combustibles (wood, paper and oil).
- ► Contamination may cause containers to explode.

SODIUM BROMATE Page 4 of 6

Spills and Emergencies

If employees are required to clean-up spills, they must be properly trained and equipped. The OSHA Hazardous Waste Operations and Emergency Response Standard (29 CFR 1910.120) may apply.

If **Sodium Bromate** is spilled, take the following steps:

- Evacuate personnel and secure and control entrance to the area.
- ▶ Eliminate all ignition sources.
- Moisten spilled material first or use a HEPA-filter vacuum for clean-up and place into sealed containers for disposal. DO NOT use combustible absorbents.
- ▶ Ventilate and wash area after clean-up is complete.
- ▶ DO NOT wash into sewer.
- ▶ It may be necessary to contain and dispose of **Sodium Bromate** as a HAZARDOUS WASTE. Contact your state
 Department of Environmental Protection (DEP) or your
 regional office of the federal Environmental Protection
 Agency (EPA) for specific recommendations.

Handling and Storage

Prior to working with **Sodium Bromate** you should be trained on its proper handling and storage.

- ➤ Sodium Bromate reacts violently with REDUCING AGENTS (such as LITHIUM, SODIUM, POTASSIUM and their HYDRIDES); COMBUSTIBLE MATERIALS; ORGANICS (such as OIL, FAT, GREASE and FUELS); METAL POWDERS (such as ALUMINUM, ARSENIC and COPPER); POTASSIUM; METAL SULFIDES; CARBON; SUGAR; and AMMONIUM SALTS.
- ► Sodium Bromate will become shock sensitive if contaminated with ORGANIC MATERIALS, METALS or CARBON.
- Store in tightly closed containers in a cool, well-ventilated area.

Occupational Health Information Resources

The New Jersey Department of Health offers multiple services in occupational health. These services include providing informational resources, educational materials, public presentations, and industrial hygiene and medical investigations and evaluations.

For more information, please contact:

New Jersey Department of Health Right to Know

PO Box 368

Trenton, NJ 08625-0368 Phone: 609-984-2202 Fax: 609-984-7407

E-mail: rtk@doh.state.nj.us

Web address: http://www.nj.gov/health/eoh/rtkweb

The Right to Know Hazardous Substance Fact Sheets are not intended to be copied and sold for commercial purposes.

SODIUM BROMATE Page 5 of 6

GLOSSARY

ACGIH is the American Conference of Governmental Industrial Hygienists. They publish guidelines called Threshold Limit Values (TLVs) for exposure to workplace chemicals.

Acute Exposure Guideline Levels (AEGLs) are established by the EPA. They describe the risk to humans resulting from once-in-a lifetime, or rare, exposure to airborne chemicals.

Boiling point is the temperature at which a substance can change its physical state from a liquid to a gas.

A **carcinogen** is a substance that causes cancer.

The **CAS number** is unique, identifying number, assigned by the Chemical Abstracts Service, to a specific chemical.

CFR is the Code of Federal Regulations, which are the regulations of the United States government.

A combustible substance is a solid, liquid or gas that will burn.

A **corrosive** substance is a gas, liquid or solid that causes destruction of human skin or severe corrosion of containers.

DEP is the New Jersey Department of Environmental Protection.

DOT is the Department of Transportation, the federal agency that regulates the transportation of chemicals.

EPA is the Environmental Protection Agency, the federal agency responsible for regulating environmental hazards.

ERG is the Emergency Response Guidebook. It is a guide for emergency responders for transportation emergencies involving hazardous substances.

Emergency Response Planning Guideline (ERPG) values provide estimates of concentration ranges where one reasonably might anticipate observing adverse effects.

A fetus is an unborn human or animal.

A **flammable** substance is a solid, liquid, vapor or gas that will ignite easily and burn rapidly.

The **flash point** is the temperature at which a liquid or solid gives off vapor that can form a flammable mixture with air.

IARC is the International Agency for Research on Cancer, a scientific group.

Ionization Potential is the amount of energy needed to remove an electron from an atom or molecule. It is measured in electron volts.

IRIS is the Integrated Risk Information System database on human health effects that may result from exposure to various chemicals, maintained by federal EPA.

LEL or **Lower Explosive Limit**, is the lowest concentration of a combustible substance (gas or vapor) in the air capable of continuing an explosion.

mg/m³ means milligrams of a chemical in a cubic meter of air. It is a measure of concentration (weight/volume).

A **mutagen** is a substance that causes mutations. A **mutation** is a change in the genetic material in a body cell. Mutations can lead to birth defects, miscarriages, or cancer.

NFPA is the National Fire Protection Association. It classifies substances according to their fire and explosion hazard.

NIOSH is the National Institute for Occupational Safety and Health. It tests equipment, evaluates and approves respirators, conducts studies of workplace hazards, and proposes standards to OSHA.

NTP is the National Toxicology Program which tests chemicals and reviews evidence for cancer.

OSHA is the federal Occupational Safety and Health Administration, which adopts and enforces health and safety standards.

PEOSHA is the New Jersey Public Employees Occupational Safety and Health Act, which adopts and enforces health and safety standards in public workplaces.

Permeated is the movement of chemicals through protective materials.

ppm means parts of a substance per million parts of air. It is a measure of concentration by volume in air.

Protective Action Criteria (PAC) are values established by the Department of Energy and are based on AEGLs and ERPGs. They are used for emergency planning of chemical release events.

A **reactive** substance is a solid, liquid or gas that releases energy under certain conditions.

STEL is a Short Term Exposure Limit which is usually a 15-minute exposure that should not be exceeded at any time during a work day.

A **teratogen** is a substance that causes birth defects by damaging the fetus.

UEL or **Upper Explosive Limit** is the highest concentration in air above which there is too much fuel (gas or vapor) to begin a reaction or explosion.

Vapor Density is the ratio of the weight of a given volume of one gas to the weight of another (usually *Hydrogen*), at the same temperature and pressure.

The **vapor pressure** is a force exerted by the vapor in equilibrium with the solid or liquid phase of the same substance. The higher the vapor pressure the higher concentration of the substance in air.



Right to Know Hazardous Substance Fact Sheet



Common Name: SODIUM BROMATE

Synonyms: None CAS No: 7789-38-0

Molecular Formula: NaBrO₃ RTK Substance No: 1686

Description: Colorless to white, crystalline or granular, odorless powder

HAZARD DATA		
Hazard Rating 2 - Health	Firefighting Sodium Bromate is not combustible but it is a STRONG OXIDIZER which enhances the	Reactivity Sodium Bromate reacts violently with REDUCING AGENTS (such as LITHIUM, SODIUM, POTASSIUM and
0 - Fire 0 - Reactivity DOT#: UN 1494 ERG Guide #: 141 Hazard Class: 5.1 (Oxidizer)	combustion of other substances. Use water only. DO NOT USE DRY CHEMICAL or CO ₂ extinguishing agents. POISONOUS GASES ARE PRODUCED IN FIRE, including <i>Hydrogen Bromide</i> . CONTAINERS MAY EXPLODE IN FIRE. Use water spray to keep fire-exposed containers cool.	their HYDRIDES); COMBUSTIBLE MATERIALS; ORGANICS (such as OIL, FAT, GREASE and FUELS); METAL POWDERS (such as ALUMINUM, ARSENIC and COPPER); POTASSIUM; METAL SULFIDES; CARBON; SUGAR; and AMMONIUM SALTS. Sodium Bromate will become shock sensitive if contaminated with ORGANIC MATERIALS, METALS or CARBON.
	Sodium Bromate may ignite combustibles (wood, paper and oil). Contamination may cause containers to explode.	

SPILL/LEAKS

Isolation Distance:

Spill: 25 meters (75 feet) Fire: 800 meters (1/2 mile)

Moisten spilled material first or use a HEPA-filter vacuum for clean-up and place into sealed containers for disposal. DO NOT use combustible absorbents.

DO NOT wash into sewer.

PHYSICAL PROPERTIES

Odor Threshold: Odorless

Flash Point: Noncombustible
Specific Gravity: 3.34 (water = 1)

Water Solubility: Soluble

Boiling Point: 718°F (381°C) (Decomposes)

Molecular Weight: 150.9

EXPOSURE LIMITS

The Protective Action Criteria values are:

PAC-1 = 1.5 mg/m^3 PAC-2 = 12.5 mg/m^3 PAC-3 = 60 mg/m^3

PROTECTIVE EQUIPMENT

Gloves: Nitrile and Natural Rubber

Coveralls: Tyvek®

Respirator: >1.5 mg/m³ - SCBA

HEALTH EFFECTS

Eyes: Irritation
Skin: Irritation

Inhalation: Nose, throat and lung irritation with

coughing, wheezing and severe shortness of breath (pulmonary edema) Headache, fatique and blue color to the

skin and lips (*methemoglobinemia*)

FIRST AID AND DECONTAMINATION

Remove the person from exposure.

Flush eyes with large amounts of water for at least 15 minutes. Remove contact lenses if worn.

Quickly remove contaminated clothing and wash contaminated skin with large amounts of water.

Begin artificial respiration if breathing has stopped and CPR if necessary. **Transfer** promptly to a medical facility.

Transfer promptly to a medical facility.

Medical observation is recommended as symptoms may be delayed.